

### **AMENDMENTS TO THE CLAIMS**

Please amend the claims as follows:

1. (Original) A preformed foam bun for an automobile high-back seat, comprising:  
a front portion that provides cushion and shape of the front portion of the high-back seat;  
a rear portion joined to the front portion so as to define an interior space for receiving an internal frame of the high-back seat;  
wherein the rear portion defines an opening dimensioned to receive a utility or an entertainment component therein.
2. (Original) The foam bun of Claim 1, further comprising a mound about the opening such that the mound increases the depth of the opening.
3. (Original) The foam bun of Claim 2, wherein the increased depth allows flush mounting of the utility or the entertainment component with respect to the mound.
4. (Original) The foam bun of Claim 3, wherein the front portion of the foam bun is contoured with respect to the mound so as to generally maintain a desired thickness of the foam bun about the opening.
5. (Original) The foam bun of Claim 1, further comprising a wire pathway defined by the foam bun such that the pathway allows one or more wires to be routed from a first location adjacent the opening to a second location on the foam bun thereby allowing the foam bun to be prewired for easier wiring of the utility or the entertainment component installed in the opening.
6. (Original) The foam bun of Claim 1, wherein the foam bun is formed from urethane.
7. (Original) The foam bun of Claim 6, wherein the opening is formed during molding of the foam bun.
8. (Original) The foam bun of Claim 1, wherein the utility component comprises a storage compartment.
9. (Original) The foam bun of Claim 8, wherein the storage compartment includes a cover.

**Appl. No.** : 10/765,464  
**Filed** : January 26, 2004

10. (Original) The foam bun of Claim 1, wherein the entertainment component includes a video screen.

11. (Original) The foam bun of Claim 10, wherein the entertainment compartment includes a cover to hide the video screen from view when the video screen is not in use.

12. (Original) A high-back seat for an automobile, comprising:  
an internal frame that provides structural integrity of the seat;  
a seat cover that covers the seat; and

a preformed bun interposed between the internal frame and the seat cover, wherein the bun defines an integral opening at its rear portion such that the opening allows installation of a utility or an entertainment component therein.

13. (Original) The seat of Claim 12, wherein the bun is contoured about the opening so as to provide sufficient depth for flush mounting of the utility or the entertainment component.

14. (Original) The seat of Claim 13, wherein the contouring of the bun comprises a mound at the rear portion of the bun about the opening.

15. (Original) The seat of Claim 14, wherein the contouring of the bun further comprises a reduction in the front portion of the bun about the opening to generally maintain a desired thickness of the bun about the opening.

16. (Original) The seat of Claim 12, wherein the bun further defines a wire pathway that allows one or more wires to be routed from a first location adjacent the opening to a second location on the bun thereby allowing the bun to be prewired for easier wiring of the utility or the entertainment component installed in the opening.

17. (Original) The seat of Claim 12, wherein the bun is formed from urethane foam.

18. (Original) The seat of Claim 17, wherein the opening is formed during molding of the foam bun.

19. (Original) The seat of Claim 12, wherein the utility component comprises a storage compartment.

20. (Original) The seat of Claim 19, wherein the storage compartment includes a cover.

21. (Original) The seat of Claim 12, wherein the entertainment component includes a video screen.

**Appl. No.** : **10/765,464**  
**Filed** : **January 26, 2004**

22. (Original) The seat of Claim 21, wherein the entertainment compartment includes a cover to hide the video screen from view when the video screen is not in use.

23. (Original) A foam bun for an automobile high-back seat, comprising:  
a front portion that provides cushion and shape of the front portion of the high-back seat;  
a rear portion joined to the front portion so as to define an interior space for receiving an internal frame of the high-back seat;  
an opening defined by the rear portion of the seat wherein the opening allows installation of a utility or an entertainment component therein; and  
a mound formed about the opening to increase the depth of the opening.

24. (Original) A preformed foam bun for an automobile high-back seat, comprising:  
a front portion that provides cushion and shape of the front portion of the high-back seat;  
a rear portion joined to the front portion so as to define an interior space for receiving an internal frame of the high-back seat;  
an opening defined by the rear portion of the seat wherein the opening allows installation of a utility or an entertainment component therein; and  
a wire pathway defined by the foam bun such that the pathway allows one or more wires to be routed from a first location adjacent the opening to a second location on the foam bun thereby allowing the foam bun to be prewired for easier wiring of the utility or the entertainment component installed in the opening.

Claims 25-27 Canceled.